

GEODRL™ Drill Pipe

GEODRL™ Drill Pipe - Represents a breakthrough in geothermal drilling technology that is revolutionizing the industry. By using our advanced technology, and engineering designs, you will be able to tackle even the most challenging rock formations, high temperatures, and harsh well conditions, making your geothermal projects not only economical but also incredibly successful.

GEODRL™ offers revolutionary, cutting-edge technology founded on an unrivaled expertise in geothermal drilling. Our team of industry professionals is ready to provide comprehensive support and tailor solutions to your specific project needs. Working together, we can achieve exceptional drilling performance and unlock the full potential of your geothermal projects.



Features & Benefits

Advanced Material Science

- Crafted from cutting-edge materials
- Designed to withstand extreme temperatures
- Resistant to corrosion
- Exceptional durability
- Maximizes equipment lifespan
- Arrogate Defender™ is the leading external coating for minimizing pipe corrosion in all drilling, completion and open-water environments

Enhanced Performance

- Superior torque transmission
- Insulating ID coating for thermodynamic and mechanical performance
- Efficient power transfer
- Allows for deeper and faster drilling
- Saves time and resources

Innovative Design

- Optimized weight distribution
- Hole size optimization
- Improved rigidity and stability
- Reduced vibration
- Enhanced control
- Improved drilling accuracy



Technical Specifications

OD (in)	Wall (in)	Grade	Tool Joint		Connection Name
			OD (in)	ID (in)	
4.50	0.337	S-135	5.375	3.000	GEO 452™
4.75	0.350	S-135	5.625	3.000	GEO 463™
5.00	0.362	S-135	5.875	3.250	GEO 487™
	0.362	S-135	6.625	3.500	GEO 541™
	0.362	S-135	6.625	3.750	GEO 528™
	0.415	S-135	6.000	3.250	GEO 494™
	0.500	S-135	6.000	3.000	GEO 485™
5.25	0.500	S-135	6.250	3.375	GEO 514™
	0.362	S-135	6.625	4.000	GEO 559™
	0.415	S-135	6.250	3.500	GEO 518™
5.50	0.500	S-135	6.250	3.000	GEO 501™
	0.361	S-135	6.625	4.000	GEO 559™
	0.415	S-135	6.750	4.000	GEO 566™
5.875	0.500	S-135	6.750	3.750	GEO 557™
	0.415	S-135	7.000	4.250	GEO 591™
6.00	0.500	S-135	7.000	3.750	GEO 570™
	0.415	S-135	7.250	4.563	GEO 617™
	0.500	S-135	7.250	4.188	GEO 603™