


# UltraFlow Multi-Lateral Technology

## Black Diamond: Pioneering Efficiency in Multi-Lateral Technology

Discover a new chapter in multi-lateral technology with Black Diamond. Experience a 40% reduction in costs, sparing no aspect of your drilling operation – from casing and directional systems to bits, rigs, cuttings removal, pad construction, cementing, mud, wellhead installations, pump jacks, flow lines, to even mobilization and demobilization expenses.

Eliminate the need for intervention tools with Black Diamond's technology, streamlining your operations. Achieve a notable 50% reduction in trip count for dual laterals. Our system excels as the sole solution capable of indexing between laterals, facilitating zipper fracking and drill-out operations without the need for extra components.

Experience true versatility with Black Diamond's multi-lateral technology. Opt for frac plugs or sliding sleeves as per your operational requirements. This adaptability ensures tailored precision in each lateral, providing flexibility without compromising efficiency.



### Level 3 Junction Specifications

Casing Size <sup>1</sup> (in.)	7	9 5/8	10 3/4
Casing Weight (lb/ft)	23 - 29	40 - 53.5	50.5 - 60.7
Main Bore ID <sup>2</sup> (in.)	4.90	7.25	8.00
Lateral Hole (in.)	6.125	8.500	8.500, 9.500
Lateral ID (in.)	3.875	6.184	8.681
Pressure Rating <sup>3</sup> (psi)	12,000	10,000	10,000
Tool Composition	L-80, 13% Cr or P-110		
Window Type	Casing Exit		
TAML Level	3 & 4		

<sup>1</sup> Other sizes available on request

<sup>2</sup> ID may vary depending on connecting configuration selected

<sup>3</sup> System pressures may vary depending on connecting configuration selected

### Hydraulic Release Running Tool Specifications


Tool Size <sup>1</sup> (in.)	4 1/2	5	7	9 5/8
Tensile Load (lbs)	225,000		540,000	1,300,000
Compressional Strength Rating (lbs)	60,000		100,000	100,000
Internal/ External Pressure Rating (psi)	7,000			
Torque Rating (lbf-ft)	12,000		40,000	60,000
Maximum Temperature (°F)	325			

<sup>1</sup> Other sizes available on request

### Drop Off Mandrel & Tie Back Receptacle Specifications

Liner Size <sup>1</sup> (in)	4 1/2	5	5 1/2	7
Tool OD (in.)	5.69	5.75	8.25	8.25
Seal Bore ID (in.)	5.00	5.25	7.38	7.50
Length (ft)	10-20			
Torque Rating (lbf-ft)	12,000		40,000	60,000
Tensile Load	As Per Liner			
Tool Composition	As Required			
Internal / External Pressure	As Required			

<sup>1</sup> Other sizes available on request



**LOCATIONS**



**USA**

**BLACK DIAMOND CORPORATE**

15425 N. Freeway, Suite 350  
Houston, Texas 77090  
1.281.443.0062

**BLACK DIAMOND BROUSSARD**

1173 Old Spanish Trail, Hwy 182 N  
Broussard, LA 70518  
1.337.359.1994

**BLACK DIAMOND CONROE**

4205 FM 1485  
Conroe, TX 77306  
1.936.441.1480

**BLACK DIAMOND MWD**

2418 N Frazier Street #100  
Conroe, Texas 77303

**BLACK DIAMOND WEST TEXAS**

3510 N. County Rd 1148  
Midland, TX 79705  
1.432.689.0076

**CANADA**

**BLACK DIAMOND EDMONTON**

Wenzel Downhole Tools  
3115 – 93 Street NW  
Edmonton, AB T6N 1L7  
1.780.440.4220

**GUYANA**

**BLACK DIAMOND GEORGETOWN**

Plantation "A"  
Houston District  
East Bank Demerara  
Georgetown, Guyana

**MEXICO**

**BLACK DIAMOND VILLAHERMOSA**

Avenida San Lucas Manzana 2 Bodega 3 y 4  
Parque Logistico Industrial Tabasco  
Rancheria Anacleto Canabal 4ta. Seccion.  
Centrol, Tabasco C.P. 86287  
+52 993 688 8579

**BLACK DIAMOND TAMPICO**

Carretera federal 20 de Noviembre km 18.7  
Congregacion Anahuac  
Pueblo Viejo, Ver., C.P. 92035  
+52 993 688 8579

**MIDDLE EAST**

**BLACK DIAMOND ABU DHABI**

Wenzel Downhole Tools  
Al Markaz Industrial Area  
Waha Land, LT01 B25-32  
Abu Dhabi, U.A.E.  
+971 2 585 2800