

Power Section Specifications

Motor Size (in)	Power Config.	Speed Range (rpm)	Rotation (rev/gal)	Torque Slope (rev/gal)	Max Diff. Pressure (psi)	Stall Torque (ft. lbs)	Max Power (hp)
3 1/8	7/8 2.5	120-260	1.24	1.97	290	1,830	50
4 3/4	5/6 8.3	300	1	2.55	1,960	4,980	280
4 3/4	7/8 2.6	39-79	0.263	8.97	590	7,880	68
4 3/4	7/8 3.8	78-130	0.521	5.2	860	6,670	96
5	5/6 8.3	100-300	1	2.55	1,660	6,670	127
5	7/8 2.6	39-79	0.263	8.97	590	7,880	68
5 1/4	7/8 8.3	190	0.48	4.8	1,960	9,370	340
5 1/2	7/8 8.5	120-220	0.5	5.087	1,910	14,590	348
5 3/4	6/7 10.6	180-300	0.6	4.29	2,390	15,350	490
6 1/2	7/8 6.0	86-173	0.288	9.3	1,350	18,830	357
6 3/4	7/8 5.7	73-157	0.242	10.7	1,280	20,580	350
6 3/4	7/8 6.0	86-173	0.288	9.3	1,350	18,830	357
7	6/7 12.1	140-300	0.4	6.44	2,720	26,300	899
7 1/4	6/7 12.1	140-300	0.4	6.44	2,720	26,300	899
8	7/8 3.4	36-60	0.087	28.19	800	22,530	340
8 1/4	7/8 7.0	66-166	0.166	15.32	1,580	36,200	680
9 5/8	5/6 4.0	66-130	0.108	21.37	900	28,850	434
9 5/8	7/8 4.8	66-132	0.11	22.27	1,080	36,070	529